

P25 Conventional and Phase 1/2 Trunking Rugged Mobile Radio with Superior Class Leading Audio

The IC-F7540 is a P25-compliant 700/800 MHz radio, and combines a high visibility color LCD, improved user interface and, loud and clear audio, all within the radio's rugged construction. The IC-F7540 can be upgraded to P25 Phase 1 trunking and Phase 2 trunking with a license key(s). Standard GPS receiver, Bluetooth®, voice recorder and microSD card slot further bring a new set of innovative and clever functions.

P25 Phase 1 conventional, trunking* and Phase 2 trunking* capable

High visibility color LCD in both natural and low lighting conditions

DHS P25 CAP certified (TIA-102) compliant for multiple vendor interoperability

Built-in Bluetooth®, voice recording, and P25 packet data (GPS)* functions

Optional FIPS 140-2 compliant AES encryption unit*

IP55 water jet resistant and dust protection

P25 voting scan* (P25 conventional)

Enhanced dual-rate AMBE+2™ vocoder

Up to 1024 channel capacity with 128 zones

Optional dual head and COMMANDMIC™ configurations

* License key upgrade required




IC-F7540



General Features

- 700/800 MHz frequency bands
- 1024 channels / 128 zones
- High resolution color LCD and intuitive user interface
- Large sized functions and four-direction buttons
- Day and night mode display settings



Day and night mode example

- Functions and menu items can be set in a language other than English (For example, French, Spanish, or Russian)
- MIL-STD-810 G such as shock, vibration and temperature
- IP55, water jet resistance and dust protection
- Front panel programming option (ISL-P25FP License key required)
- DTMF autodial

Operating Mode

- P25 Phase 1 Conventional
- P25 Phase 1 Trunking (ISL-P25TR License key required)
- P25 Phase 2 Trunking (ISL-P25P2 and ISL-P25TR License keys required)
- Analog mode
- Analog/Digital mixed operation

Digital Functions (Voice and Data)

- Over-the-Air Programming (OTAP) function (Conventional only) (CS-OTPM2 manager software required)
- Individual, Group calls
- Unit ID and Talkgroup display on receive
- Status update and Status query
- Short data messages (Up to 100 characters)
- GPS position and Transparent Data transmission (ISL-P25DS License key and UX-241 GPS antenna required)
- Call Alert
- Phone number list
- Call Log

Analog Functions

- CTCSS and DTCS tone
- 2-Tone
- MDC functions

Security and Safety

- Optional UT-125FIPS FIPS 140-2 compliant AES/DES encryption unit and UT-134 non-FIPS AES/DES unit (ISL-P25AES License key required for AES encryption)
- Over-the-Air Rekeying (OTAR)
- Analog inversion voice scrambler (16-codes)
- Power ON password
- Tactical group temporarily reconfigures user groups
- Radio Stun/Kill/Revive
- Remote monitor
- Radio check
- Power OFF emergency
- Emergency button
- Lone worker function
- Advanced System Key (ASK) protects the radio from unauthorized programming (trunking system)

Scan Functions

- Priority scan • Talkgroup scan
- Voting scan for automatically selecting optimal repeater site (ISL-P25VS License key required)

Voice/Audio Functions

- Voice announcement (Channel number and zone)
- VOX function for hands-free operation
- Voice recording/playback is saved to a microSD card (Up to 500 hours with a 32 GB card) (User supplied)
- TX/RX active noise canceler
- TX/RX audio equalizer (Flat, high/mid/low boost, low cut)
- AF volume equalizing function adds high-pass filter to provide clear, intelligible audio, when increases the volume
- Adjustable analog and digital volume level
- Programmable ringer beep

Hardware Features

- Built-in Bluetooth® (Version 2.1 + EDR) for wireless audio and data
- Third-party wireless Bluetooth® headset (Like a 3M™ Peltor™ WS™ 5) can be used
- Wireless radio programming over Bluetooth®
- USB connector for data transfer or microSD card reader mode
- Programmable D-SUB connector for external PTT, channel, horn, PA/RX speaker, ignition switch and dimmer control
- Internal clock with time auto adjustment
- Low voltage alert
- Optional detached controller, dual head controller or COMMANDMIC™ configurations
- Intercom function between dual head controller or COMMANDMIC™

		IC-F7540
GENERAL		
Frequency coverage (* Depends on the transceiver version)	USA	769–775 MHz (RX/TX), 799–805 MHz (TX), 806–824 MHz (TX), 851–869 MHz (RX/TX)
	EXP	764–776 MHz (RX/TX), 794–806 MHz (TX), 806–825 MHz (TX), 851–870 MHz (RX/TX)
Number of channels		1024 channels /128 zones
Type of emission (* Depends on the transceiver version)		16K0F3E, 14K0F3E, 11K0F3E, 8K50F3E, 8K10F1E/F1D, 8K10F1W
Power supply requirement		13.6 V DC nominal
Current drain (approx.)	TX	14.0 A (at 35 W)
	RX	1.2 A /400 mA (Max. audio (external SP)/Standby)
Antenna impedance		50 Ω
Operating temperature range		–30 °C to +60 °C, –22 °F to +140 °F
Dimensions (W × H × D, Projections not included)		174 × 55 × 150 mm, 6.9 × 2.2 × 5.9 in
Weight (approx.)		1500 g, 3.3 lb
TRANSMITTER		
Output power (Hi, L2, L1)	USA	30 W, 15 W, 2 W (769–775, 799–805 MHz), 35 W, 15 W, 2 W (806–824, 851–869 MHz)
	EXP	30 W, 15 W, 2 W (764–776, 794–806 MHz), 35 W, 15 W, 2 W (806–825, 851–870 MHz)
Frequency stability		±1.0 ppm
Spurious emissions		80 dB typical
FSK error		1% typical (C4FM), 3% typical (H-CPM)
Maximum frequency deviation		±5.0 kHz (25 kHz), ±4.0 kHz (20 kHz), ±2.5 kHz (12.5 kHz)
FM hum and noise		55 dB typical (25/20/12.5 kHz)
Audio harmonic distortion		0.5% typical (AF 1kHz 40% deviation)
RECEIVER		
Sensitivity	Digital (5% BER)	0.22 μV typical (C4FM/H-DQPSK)
	Analog (12 dB SINAD)	0.22 μV typical (25/20/12.5 kHz)
Adjacent channel selectivity	Digital	65 dB typ. (@C4FM, TIA-102)
	Analog	63 dB typ. (@H-DQPSK, TIA-102)
		75/70/57 dB typical (25/20/12.5 kHz, TIA-603B)
Spurious response rejection		75/70/68 dB typical (25/20/12.5 kHz, TIA-603)
Intermodulation rejection		80 dB typical
Audio output power	Digital	75 dB typical (C4FM/H-DQPSK)
	Analog	75 dB typical (25/20/12.5 kHz)
Internal SP		4.0 W typical (at 5% distortion with 4 Ω load)
External SP		4.0 W typical (at 5% distortion with 4 Ω load)

Measurements made in accordance with TIA-102 (P25), TIA-603 (FM Wide/middle/narrow).

All stated specifications are subject to change without notice or obligation.

Applicable U.S. Military Specifications & IP Rating

Standard	MIL 810G	
	Method	Procedure
Low Pressure	500.5	I, II
High Temperature	501.5	I, II
Low Temperature	502.5	I, II
Temperature Shock	503.5	I-C
Solar Radiation	505.5	I
Rain Blowing/Drip	506.5	I, III
Humidity	507.5	II
Salt Fog	509.5	–
Dust Blowing	510.5	I
Vibration	514.6	I
Shock	516.6	I, IV

Also meets equivalent MIL-STD-810-C, -D, -E and -F.

Ingress Protection Standard	
Dust & Water	IP55 (Dust-protection and water jet resistance)

Supplied accessories: (May differ depending on the transceiver version)	
• Hand microphone, HM-220	• DC power cable
• Mounting bracket kit	• Microphone hanger

HAND MICROPHONES AND DESKTOP MICROPHONE

HM-220: Heavy duty microphone. IP54 protection.
HM-220T: Heavy duty microphone with DTMF keypad. IP54 protection.
HM-221: Hand microphone with emergency button. IP55 protection.
HM-221T: Hand microphone with DTMF keypad and emergency button. IP55 protection.
SM-29: Desktop microphone with monitor and monitor lock buttons.



COMMANDMIC™ AND SEPARATION KITS

HM-218: COMMANDMIC™ for use with the RMK-5. IP55 protection.
RMK-5: Separation kit. For detached controller configuration.
RMK-7: Dual-head separation kit. Separation kit and secondary controller for dual head configuration.



SEPARATION CABLES

OPC-2364: 1.9 m, 6.2 ft separation cable for RMK-5 or RMK-7.
OPC-2365: 3 m, 9.8 ft separation cable for RMK-5 or RMK-7.
OPC-2366: 5 m, 16.4 ft separation cable for RMK-5 or RMK-7.
OPC-2367: 8 m, 26.2 ft separation cable for RMK-5 or RMK-7.
OPC-2373: 1.9 m, 6.2 ft separation cable for HM-218, COMMANDMIC™.
OPC-2374: 8 m, 26.2 ft separation cable for HM-218, COMMANDMIC™.

HEADSET

VS-3: Bluetooth® headset.



EXTERNAL SPEAKERS

SP-30: External speaker
 Cable length 2.6 m, 8.5 ft
SP-35/L: Compact external speaker
 SP-35 cable length: 2 m, 6.6 ft
 SP-35L cable length: 6 m, 19.7 ft



GPS ANTENNA

UX-241: External GPS antenna
 Cable length 5 m, 16.4 ft



AES/DES ENCRYPTION UNITS

UT-134: AES/DES encryption unit
UT-125FIPS: AES/DES encryption unit (FIPS compliant)
 ISL-P25AES is additionally required for AES encryption.
 No additional software is needed for DES encryption.
KVL125: DES/AES keyloader
OPC-IAKVL1: KVL125 keyloading cable (Requires IAOPC1075 and RJ45 adapter.)
IAOPC1075: KVL3000/KVL4000 Encryption Keyloading Cable (Requires OPC-1534 and RJ45 adapter)



ZONE COPY, PROGRAMMING AND DC POWER CABLES

OPC-2362: Zone copy cable. Mobile to handheld cable.
OPC-2363: Programming cable
OPC-1132: DC power cable. Cable length 3 m, 9.8 ft
OPC-347: DC power cable. Cable length 7 m, 23 ft



SOFTWARE AND ACTIVATION KEYS

CS-F7500: Programming software
CS-F7500ASK: P25 advanced system key manager software (Available only to trunking system owners.)
CS-OTPM2: OTAP manager software
ISL-P25VS: P25 conventional voting scan upgrade key
ISL-P25TR: P25 Phase 1 trunking upgrade key
ISL-P25P2: P25 Phase 2 trunking upgrade key. ISL-P25TR P25 Phase 1 license key is also required.
ISL-P25DS: P25 packet data service (GPS and transparent data) upgrade key
ISL-P25AES: AES encryption upgrade key. Either UT-134 or UT-125FIPS is required.
ISL-P25FP: Front panel programming key
IASKF7P: P25 advanced system owner master key (Available only to trunking system owners.)
IASKF7S: P25 accessory advanced system key (Required for trunking programming.)

Some options may not be available in some countries. Please ask your dealer for details.



Detached Controller
 Optional RMK-5 and separation cable required.



Dual Head Controller
 Optional RMK-7, hand microphone and separation cables required.



COMMANDMIC™ and Detached Controller
 Optional RMK-5, COMMANDMIC, HM-218 and separation cables required.

Icom, Icom Inc. and the Icom logo are registered trademarks of Icom Incorporated (Japan) in Japan, the United States, the United Kingdom, Germany, France, Spain, Russia, Australia, New Zealand and/or other countries. COMMANDMIC is a trademark of Icom Incorporated. The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by Icom Inc. is under license. AMBE+2 is a trademark and property of Digital Voice Systems, Inc. 3M, Peltor, and WS are trademarks of 3M Company. All other trademarks are the properties of their respective holders.

Icom Inc. 1-1-32, Kamiminami, Hirano-Ku, Osaka 547-0003, Japan Phone: +81 (06) 6793 5302 Fax: +81 (06) 6793 0013 www.icom.co.jp/world **Count on us!**

Icom America Inc.
www.icomamerica.com

Icom (Europe) GmbH
www.icomeurope.com

Icom (Australia) Pty. Ltd.
www.icom.net.au

Your local distributor/dealer:

Icom Canada
www.icomcanada.com

Icom Spain S.L.
www.icomspain.com

Shanghai Icom Ltd.
www.bjicom.com

Icom Brazil
 E-mail: sales@icombrasil.com

Icom (UK) Ltd.
www.icomuk.co.uk

Icom France s.a.s.
www.icom-france.com